




Laptop-Style Compact Keyboard with Integrated Trackpad :

Mechanical Drawing :



Key Functions :

Functions	Keys
NumLock	Fn + Esc
Mute	Fn + F1
Volume -	Fn + F2
Volume +	Fn + F3
Backward	Fn + F4
Play / Pause	Fn + F5
Forward	Fn + F6
LCD Power Enable	Fn + F7
Project Screen	Fn + F8
Search	Fn + F9
LTE Disable	Fn + 7
Touch Disable	Fn + T
VGA Disable	Fn + G
Home	Fn + Left Arrow
Page Up	Fn + Up Arrow
Page Down	Fn + Down Arrow
End	Fn + Right Arrow

Technical Specifications :

Electrical :

- Power Supply : USB: +5V/DC
- Current Input : USB: 50mA
- Interface : USB Compatible with all Microsoft Windows /MAC /Linux
- USB Cable Length : Approx. 1.8Meter

Mechanical :

- Number of Keys: 80keys
- Individual key life cycle: 3 million
- Key actuation force: 80-120g ±20g
- Material: ABS

Others :

- Operating temperature: 20°C to +60°C
- Storage temperature: -25°C to +70°C
- Operating humidity: 90-95% Resistant
- Dimensions (L-W-T): 312.9mm x 221.4mm x 6.9mm(Excluding key height) Tol. ±2mm

Tact Switch Specification :

- Maximum Voltage: 12 VDC
- Maximum Current DC: 50 mA Dielectric
- Strength: 250 vA C (1mn) Contact
- Resistance: $\leq 100 \text{ m}\Omega$ initial Insulation
- Resistance: $\geq 100 \text{ M}\Omega$
- Bounce Time: $\leq 10 \text{ ms}$
- Operating Temperature: -40°C to 85°C

Physical Parameter :

- Active Area - 65.0 x 49.0mm
- Operating Temperature: -40°C to 85°C
- Touch Type: Capacitive
- Interface: USB
- Mechanical Buttons: 2(Right Click & Left Click)

Standard Operation:

- Left Click.
- Double Click.
- Click and Drag.
- Right Click.
- Scroll Up/Down.
- Zoom In/Out.

USB Pinout Table :

USB	
PIN	Definition
1	VDD/5V
2	D-
3	D+
4	GND

———— End : ————